Superseding: New

Effective Date: February 1, 2022

Page: 1 of 3

# Swivel Hook Assemblies, 1.63 Metric Ton (WLL)



#### 1. Scope

This standard covers the requirements for 1.63 metric ton working load limit (WLL), swivel hook assemblies and replacement parts.

Spools are also known as thimbles.

This standard applies to the following Seattle City Light (SCL) stock numbers:

Stock No.	Description		
014791	Swivel hook assembly (includes shield and spool)		
014792	Replacement nylon shield		
014793	Replacement nylon spool		
014794	Replacement latch kit		

# 2. Application

Swivel hook assemblies are intended to be attached to rope soft eyes.

Swivel hook assemblies extend the life of rope soft eyes by keeping the rope positioned correctly on spool, providing a wider bearing surface resulting in an increased area for load distribution, and reducing abrasion.

Swivel hook spools are designed for synthetic rope sizes 9/16 to 5/8 inch.

# 3. Industry Standards

Swivel hooks shall meet the applicable requirements of the latest revision of the following industry standard:

**ASME B30.10**; Hooks - Safety Standard for Cableways, Cranes, Derricks, Hoists, Hooks, Jacks, and Slings

Standard Coordinator John Shipek Standards Engineering Supervisor John Shipek

Division Director Andrew Strong

goldfil

gold fil

Mesta

Standard Number: **7272.16** 

Seattle City Light MATERIAL STANDARD

Swivel Hook Assemblies, 1.63 Metric Ton (WLL)

Superseding: New Effective Date: February 1, 2022

Page: 2 of 3

# 4. Requirements

#### 4.1 Assemblies

Assemblies shall be composed of a swivel hook, a shield, and a spool as described in Sections 4.2, 4.3, and 4.4.

#### 4.2 Swivel Hook

#### Swivel hooks:

- Shall include a latch
- Shall be forged alloy steel
- Have a working load limit (WLL) of 1.63 metric tons
- Can be proof tested two times the WLL

WLL shall be based on a 5:1 safety factor.

WLL shall be stamped on each side.

#### 4.3 Shields

#### Shields shall be:

- Nylon
- Red

# 4.4 Spools

# Spools shall be:

- Nylon
- Designed for synthetic rope sizes 9/16 to 5/8 inch

# 4.5 Latch Kits

Latch kits shall be composed of the following:

- Latch
- High cycle, long life spring
- Cotter pin
- Through bolt
- Nut

# Figure 4.5. Latch Kit



Standard Number: **7272.16** 

Seattle City Light

MATERIAL STANDARD

Swivel Hook Assemblies, 1.63 Metric Ton (WLL)

Superseding: New Effective Date: February 1, 2022

Page: 3 of 3

# 5. Packaging

Swivel assemblies shall be packaged and shipped assembled.

Swivel assemblies and replacement parts shall be packaged to prevent damage during shipping, handling, and inside storage.

Individual packages shall be legibly marked with:

- Manufacturer identification
- Product description
- Seattle City Light stock number

Each shipping container shall be legibly marked with the following information:

Seattle City Light purchase order number

# 6. Issuance

Stock unit: EA

#### 7. Approved Manufacturers

Stock No.	Description	Manufacturer	Product Code
014791	Assembly	Crosby	S-3319/1002054
014792	Replacement shield, red	Samson	Nylite Shield 969
014793	Replacement spool	Samson	Nylite Spool Size 2
014794	Replacement latch kit	Crosby	1096468

#### 8. Sources

Samson Utility Product Guide, 2016/2017, YGS:MSW 109598 500 8/2017

**Shipek, John**, SCL Standards Supervisor, originator, and subject matter expert for 7272.16

www.thecrosbygroup.com/catalog/