Standard Number: **7658.30** 

Superseding: New

Effective Date: March 15, 2019

Page: 1 of 2

# Labeling Tape, Reflective, Brady Labelizer System







## 1. Scope

This standard covers the requirements for labeling tape used with the Brady Labelizer label maker.

This standard applies to the following Seattle City Light (SCL) stock numbers:

Stock No.	Description
010389	Labeling Tape, Reflective White, 2.2" x 75'
010390	Labeling Tape, Reflective Yellow, 2.2" x 58'

## 2. Application

Brady labeling tape is used for printing labels for indoor or outdoor equipment as well as racks and shelves where high visibility is critical.

The Brady Labelizer and Brady GlobalMark label maker systems, for which SCL stocks labeling tape, are legacy systems no longer being manufactured.

See SCL 7658.40 for labeling tape for the Brady Globalmark.

### 3. Requirements

Product requirements shall be as defined in Section 6.

Standards Coordinator Ponet Neuansourinh Standards Supervisor John Shipek Unit Director Andrew Strong

Mesta

Standard Number: **7658.30** 

Seattle City Light

MATERIAL STANDARD

Labeling Tape, Reflective, Brady Labelizer System

Superseding: New Effective Date: March 15, 2019

Page: 2 of 2

## 4. Packaging

Product shall be packaged to prevent damage during shipping, handling, and storage.

Individual packages shall be legibly marked with:

- Manufacturer name
- Manufacturer catalog number
- Product description
- Seattle City Light stock number

Shipping containers shall be legibly marked with:

- Manufacturer name
- Seattle City Light purchase order number

#### 5. Issuance

Stock Unit: EA

## 6. Approved Manufacturers

Stock No.	Description	Brady Part No.	
010389	Labeling tape, Labelizer:  Reflective white  Cassette Plastic 2.2" x 75' Minimum application temperature: 50°F Service Temperature: 40°F to 158°F Average outdoor durability: 4-6 years	64740	POLICE OF THE STATE OF THE STAT
010390	Labeling tape, Labelizer:  Reflective yellow Cassette Plastic 2.2" x 58' Minimum application temperature: 50°F Service Temperature: 40°F to 158°F Average outdoor durability: 4-6 years	64404	



**Neuansourinh, Ponet**; SCL Standards Engineer and originator of 7658.30 (ponet.neuansourinh@seattle.gov)

SCL Stock Catalog page 76-17; May 15, 2014

www.bradyid.com